



Model with remote control for easy operation from the drivers cabin.

The TF 160/150 is the newest unit in the IGEBA product range. As a new version of the TF 160 HD it is equipped with a 150L solution tank thus offering 2.5 times more capacity than its smaller brother. With the special attachment even water based solutions can be applied with excellent results.

Technical Specifications

Empty weight in kg	120
Dimensions L x W x H in cm	260 x 80 x 91
Solution Tank capacity in l	150
Fuel Tank capacity in l	20
Performance of combustion chamber in KW/HP	82.2 / 112
Fuel consumption, approx. in l/h	9.5
Average flow rate in l/h (oil based)	120
Max. flow rate in l/h (oil based)	160
Flow rate with water in l/h	80
Efficient horizontal reach in closed rooms with water and carrier	120
Efficient horizontal reach in closed rooms with water	80
Energy supply	12V DC car battery
Pressure in solution tank in bar approx.	0.25


Regional Office:


Agro Technic Pte Ltd
 No. 32 Ang Mo Kio Industrial Park 2 #01-01/02
 Sing Industrial Complex Singapore 569510
 Tel: (65) 6482 1828 Fax: (65) 6481 2631
 Email: agro@agrotech.com.sg Website: www.agrofog.com

Malaysia Office:

Agrofog Sdn. Bhd

No. 18 Jalan PJS 11/14 Bandar Sunway Industrial Park
 47500 Subang Jaya Selangor Malaysia
 Tel: 03-5638 8486 Fax: 03-5638 8491
 Penang: 04-6411734
 Email: agro@agrofog.com.my Website: www.agrofog.com